

TTE UTP FTP CAT 5E CAT 6 CABLE

High quality new LAN cables line - TTE prepared for every possible application. TTE cables are based on cat5e and cat6 standards. All cables have copper wires and are produced with accordance to EN 50173 standards.

**Main features:**

- the highest quality materials
- parameters exceeding the requirements of category 5e and 6 EN 50173
- pre and post-production quality control of raw materials and final product
- meter marker, pullout box
- single-wire copper conductors with a diameter of 0.55 mm (23 according to AWG) - cat6
- single-wire copper conductors with a diameter of 0.50 mm - cat5e
- conductors twisted into pairs
- cable sheath made of PVC or LSZH
- error in print size max. 0.5%

TECHNICAL PARAMETERS

TYPE	Units	TTE UTP5e	TTE FTP5e	TTE UTP6	TTE FTP6
Cable standard	/	U/UTP cat 5e	F/UTP cat 5e	U/UTP cat 6	F/UTP cat 6
CPR fire reaction	/	Eca	Eca	Dca s2,d1,a1	Dca s2,d1,a1
Wires material	/	Solid Bare Copper	Solid Bare Copper	Solid Bare Copper	Solid Bare Copper
Wires diameter	mm	0.50±0.015	0.50±0.015	0.55±0.015	0.55±0.015
Screening	/	none	Outer Al foil	none	Outer Al foil
Insulation material	/	HDPE	HDPE	HDPE	HDPE
Jacket material	/	PVC	PVC	LSZH	LSZH
Rip cord	/	YES	YES	YES	YES
Frequency range	MHz	100	100	250	250
Package	/	pullout box 305m	pullout box 305m	pullout box 305m	pullout box 305m
Index	/	WKA-0301-025-01	WKA-0301-026-01	WKA-0302-010-01	WKA-0302-020-01