

GSF OUTLETS



New line of TV and SAT for installation in ready-made systems as well as individually flush-mounted and surface-mounted. They will work great in installations in multi-family buildings and wherever radio-television and satellite signals are distributed.

The socket has a male IEC connector for R and TV signals (5-862MHz) and female F connectors for SAT signals (950-2400MHz). The sockets in the set include screws and expanding jaws for mounting in round and square boxes.

Available accessories:

GS-R - cover - flush-mounted, individual installation

GS-W - base - surface-mounted, individual installation (purchase of GS-R is required for complete set)



MAIN FEATURES:

- Casing: High-quality cast housing
- Connectors: F-female + IEC male
- Ready for DVB-T2 DVB-S2/S2X reception
- Wide frequency range: 5-2400MHz
- Passing power up to 24V/0.5A through the SAT port
- Mounting: System, flush, and surface-mounted

Suggested products:

- Coaxial Cable TT 113 Cu Trishield - ensuring high quality for every TV/SAT installation
- Coaxial Cable TT 113 Cu PE Trishield - outer TT 113 cable guaranteeing resistance to UV and moisture.

TECHNICAL PARAMETERS

PARAMETERS / OUTLET TYPE	GSF 862	
	TV 5-862 MHz	SAT 950-2400 MHz
OUTPUTS		
ATTENUATION (IN-OUT) (MAX)	2,5dB	2,5dB
ISOLATION (TV / SAT) (MIN)	20dB	20dB
RETURN LOSS (MIN)	8dB	8dB
POWERING PASSING (MAX)	/	24V _{DC} /0,5A
INDEX	WPA-0105-021-01	