



## PARAMETRY TECHNICZNE

MHz	PCT-IT1W-xx							PCT-IT2W-xx						
	Tłumienie odgałęzienia [dB]													
	6	8	11	12	14	17	20	23	26	8	12	14	16	20
Tłumienie powłokowe [dB] +/- 1dB														
5-1002	2,5	2	1,5	1,5	1,2	1		1	4	2	1,4	1		
Izolacja (Tap-Tap) [dB]														
5-40	23		26	27		31	35	39	20					
41-470	23		26	27		31	35	36	26					
471-550	22		22		24	26	30	33	26					
551-750	22		22		24	26	30	33	24					
751-860	20				21	25	30	20						
861-1002	20				21	25	30	20						
Izolacja (Tap-Wyj) [dB]														
5-40	23	23	26	27		31	35	39	23	27	30	31	35	39
41-470	23		26	27		31	35	36	25	27	28	31	35	38
471-550	22	20	22		24	26	30	33	25	27	28	31	35	39
551-750	22	20	22		24	26	30	33	22	23	24	26	32	34
751-860	20				21	25	30	20	22		23	26	30	
861-1002	20	22		23			26	30	20	22		23	26	30
Tłumienie odbić (Wej/Wyj/Tap) [dB]														
5-40	16		18			20	18	16	18			20		
41-470	18		20					18	20					
471-550	18		20					18	20					
551-750	18		20					18	20					
751-860	16		18					16	18					
861-1002	16		18					16	18					

Parametry techniczne mogą ulec zmianie bez wcześniejszego powiadomienia.

[www.telmor.pl](http://www.telmor.pl)

MHz	PCT-IT3W-xx					PCT-IT4W-xx					PCT-IT8W-xx				
	Tłumienie odgałęzienia [dB]														
	10	12	16	20	24	8	12	16	20	24	12	14	17	20	23
Tłumienie przelotowe typ. [dB] +/-1dB															
5-40	4	3,5	2	1	-	3,5	2	1,2	1	n/d	4	3	1,7		
Izolacja (Tap-Tap) [dB]															
5-40	25					25					26				
41-470	25					25					23				
471-550	25					25					23				
551-750	23					22					22				
751-860	20					20					20				
861-1002	20					20					20				
Izolacja (Tap-Wyj) [dB]															
5-40	26	28	32	36	40	-	26	30	34	42	25	28	30		
41-470	24	26	30	34	40	-	28	32	36	40	24	27	28		
471-550	24	26	30	34	38	-	26	30	34	38	21	24	25		
551-750	22	24	28	32	36	-	22	26	30	34	21	24	25		
751-860	20	22	25	28	32	-	22	26	30	34	20	22	25		
861-1002	20	22	25	28	32	-	22	24	28	32	20	22	25		
Tłumienie odbić (Wej/Wyj/Tap) [dB]															
5-40	18					18					15				
41-470	18					18					18				
471-550	18					18					18				
551-750	17					16					18				
751-860	17					16					18				
861-1002	17					16					18				

Parametry techniczne mogą ulec zmianie bez wcześniejszego powiadomienia.

[www.telmor.pl](http://www.telmor.pl)

GZT TELKOM-TELMOR SP. Z O.O., ul. Schuberta 104, 80-172 Gdańsk  
tel. 58 739 59 59, e-mail: [handlowy@telmor.pl](mailto:handlowy@telmor.pl)